

Description

Ilisintech fusion splicer, color screen, standard accessories, including cleaver MAX CI-03A. English and Chinese languages menu is available.



Feature

- ◆ Slide in color screen
- ◆ Core to core fiber alignment system PAS
- ◆ 9 seconds splice time and 26 seconds tube-heat time
- ◆ Dual tube heater
- ◆ Sleeve loader design
- ◆ Large capacity battery and level meter
- ◆ Eco-friendly RoHS compliant

Specification

- ◆ 5.6 " color TFT-LCD screen monitor
- ◆ Average splicing loss: 0.02dB SM/ 0.01dB MM/0.04 dB DS/0.04 dB NZDS
- ◆ Return loss: > 60dB
- ◆ Program/splicing/heating mode: Auto and manual, 40 splicing and 13 heating
- ◆ 2000 pcs splicing data stored in the internal memory
- ◆ Cleaved length: 8~16mm
- ◆ Cladding diameter: 80~150mm
- ◆ Coating diameter: 100~1000mm
- ◆ Number of splice/heating with battery: typical 200 cycles with S-1B/ typical 400 cycles with S-SB
- ◆ Interface: USB2.0, RCA, External power
- ◆ Max. wind velocity of 15m/s
- ◆ Working altitude: 0~5000 meters
- ◆ Electrode: 3000
- ◆ Arc test: 2N/4.4N(optional)

General

- ◆ Power supply: AC100~240V, 50Hz, DC14.8V(5600mAh),
- ◆ Operating temperature: -10~50 C
- ◆ Storage temperature: -40~80 C
- ◆ Humidity: 95% (max.) no condensation
- ◆ Weight: 2.6Kg (including battery)

Keyman S1

TUOLIMA

◆ Dimension: 150(W) * 190(D) * 120(H)mm

Application

SM(ITU-T G.652), MM(ITU-T G.651), DS(ITU G.653),NZDS(ITU-T G.655)

Packing List

No	Model	Item(E)	Unit	Qty.	Remarks
1	S1	Fusion Splicer	pcs	1	Main body
2	S-1B	Battery Pack	pcs	1	Accessories
3	S-11	Battery Charger	pcs	1	Accessories
4		Carrying Case	pcs	1	Accessories
5	S-1E	Spare Electrodes	set	1	Accessories
6	S-12	Sleeve Loader	pcs	1	Accessories
7		User Manual	pcs	1	Accessories
8		AC Cord	pcs	1	Accessories
9		Alcohol Dispenser	pcs	1	Accessories
10	MAX CI-03A	Cleaver	pcs	1	Optional